

OmniSmart UPS System

Line-interactive battery backup and network power management with hospital grade plug and receptacles



Model #: OMNISMART450HG

- ▶ 450VA line interactive tower UPS
- ▶ Hospital grade plug and 4 NEMA5-15R hospital grade output receptacles
- ▶ Corrects brownouts as low as 75V and overvoltages to 147V without using battery power
- ▶ DB9 communications port

DESCRIPTION

Tripp Lite's OMNISMART450HG offers UPS protection, built-in line interactive voltage regulation, intelligent monitoring and unattended shutdown capability. 450VA power handling capacity supports computers, internetworking equipment and other critical loads during commercial power failures. Line interactive voltage regulation corrects brownouts as low as 75V and overvoltages as high as 147V back to normal 120V levels, saving battery reserves for use only during complete power failures. Includes 4 hospital grade outlets, diagnostic LEDs and built-in DB9 communications port that works with web downloadable PowerAlert Software and cabling to provide automatic unattended shutdown of connected network and PC applications.

KEY BUYING POINTS

- Ideal UPS protection for mission critical equipment and computers where hospital-grade input/output connections are required
- Provides connected equipment with continuous power during short and long duration loss of commercial power
- Line interactive voltage regulation corrects brownouts and overvoltages from 75 to 147 volts back to usable 120V output levels, without using battery power
- Hospital-grade plug and outlets offer added degree of safety to input/output connections
- Supports loads up to 450VA /280 watts
- 17 minutes half load runtime (with 225VA load), 5 minutes full load runtime (with 450VA load)
- Hospital grade input plug and 4 NEMA5-15R hospital grade output receptacles
- 1 DB9 serial port for network interface; SNMP compatible
- Surge protection and EMI/RFI noise filtering
- PowerAlert UPS monitoring and auto-shutdown software available for free download from www.tripplite.com
- Includes complete cabling for remote monitoring via PowerAlert software
- 4 diagnostic LEDs indicate AC present, on battery, voltage correction & battery low/replace
- Battery replacement door
- 2 year product warranty

TYPICAL APPLICATIONS

- Ideal UPS protection for network workstations, small office file servers and PC systems

OPTIONS & ACCESSORIES

- SNMP accessories: [SNMPWEBSOLO](#), [ENVIROSENSE](#)
- Dateline protectors: [DNET1](#), [DTEL2](#), [DCATV](#)
- Wallmount Bracket: [UPSWM](#)
- Circuit Tester: [CT120](#)
- Extended warranties: 3 Year [WEXT3-OMNI](#), 5 Year [WEXT5-OMNI](#)

PACKAGE INCLUDES

- OmniSmart 450 Hospital-Grade UPS System
- RS-232 remote monitoring cable
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	Line Interactive UPS system with hospital grade plug and outlets, meets, line interactive voltage regulation, AC surge suppression and DB9 communications port
Voltage compatibility:	120 V AC
Frequency compatibility:	60 Hz
OUTPUT	
Output volt amp capacity (VA):	450
Output watt capacity (watts):	280
Output nominal voltage:	120V nominal
Output voltage regulation:	LINE MODE: Sine wave line voltage 120V (-18% / +8%) BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation:	LINE MODE: Passes line frequency of 60Hz. +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type:	4 NEMA5-15R Hospital Grade Output Receptacles
INPUT	
Maximum input amps:	2.8A / 320 watts
Input connection type:	NEMA 5-15P Hospital-Grade
Input cord length:	6 ft, 14 gauge
Recommended electrical service:	15A 120V
BATTERY	
Full load runtime:	5 minutes (450VA)
Half load runtime:	17 minutes (225VA)
DC system voltage:	12 VDC
Typical battery lifespan:	3-6 years, depending on usage
Battery recharge rate:	2-4 hours to 90%
VOLTAGE REGULATION	
Voltage regulation description:	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 75V and overvoltages to 147V
Overvoltage correction:	Input voltages between 128 and 147V AC are reduced by 12%
Direct pass through:	Input voltages between 108 and 127V AC are passed on to connected equipment unchanged
Brownout correction:	Input voltages between 93 and 107V AC are boosted by 14%
Severe brownout correction:	Input voltages between 75 and 92V AC are boosted by 30%
LEDS ALARMS & SWITCHES	
Front panel LEDs:	4 front-panel indicator LEDs show line power status, battery power status, battery low/replace status and voltage regulation operation
Alarms:	Audible alarm indicates power failure conditions, silenceable via alarm cancel switch. Once cancelled, alarm will resume when approximately 2 minutes of battery operation remain

	(assuming full load).
Switches:	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions
SURGE / NOISE SUPPRESSION	
AC surge suppression:	Conforms to IEEE 587 / ANSI C62.41 specifications
AC suppression response time:	Instantaneous
EMI / RFI AC noise suppression:	Yes
PHYSICAL	
Shipping weight (lbs):	23
Shipping weight (kg):	10.4
Unit weight (lbs):	21
Unit weight (kg):	9.5
Unit Dimensions (HWD/in):	10.75 x 5.25 x 7.25
Unit Dimensions (HWD/cm):	27.3 x 13.3 x 18.4
Material of construction:	PVC
Form factors supported:	Tower, wall mountable with optional UPSWM accessory
Cooling method:	Convection
Battery Access:	Battery access door allows hot swap battery replacement without powering connected equipment off
ENVIRONMENTAL	
Operating Temperature:	+32 to +104 degrees Fahrenheit 0 to +40 degrees Celsius
Storage Temperature:	+5 to +122 degrees Fahrenheit -15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing
COMMUNICATIONS	
Network monitoring port:	Includes built-in basic DB9 monitoring port
Software and cabling included:	PowerAlert UPS monitoring software available via web download for all common network and standalone operating systems. Ships with 1 cable.
SNMP compatibility:	External accessory "SNMP-SOLO" SNMP / Web adapter available
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode:	2-4 milliseconds
Low voltage transfer to battery power:	75V (resets to line power as voltage increases to 79V)
High voltage transfer to battery power:	147V (resets to line power as voltage decreases to 143V)
CERTIFICATIONS	
Certifications:	UL1778 (USA, Series AGOM700KSR61), cUL (Canada), FCC Class A (emissions)
WARRANTY	
Optional coverage:	3 year, 5 year, next day and on-site warranty coverage available
Product warranty:	2 year product warranty
SPECIAL FEATURES	
Cold Start:	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance:	Attractive gray tower UPS

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.